HIGH PRODUCTIVITY TWIN FLAVOR

Raise your standards.

These floor-standing twin-flavor machines are equipped with four separate cooling circuits powered by two compressors and two motors, ensuring independent control of each hopper and cylinder. Efficient and precise, **they are the ideal solution for elevated production capacities.**

PRODUCTS:

- Soft Serve
- Frozen Yogurt



Models:
BV 261 HT, MV EASY 2, MV 255 HT,
HV EASY 2

Excellence in every detail

- **Advanced control systems**
  INCODIS 2.0, equipped with a 7” touchscreen, or ECOS, with a capacitive LCD display.
- **Freezing cylinder feed**
  Gravity or gear pump feeding to deliver excellent results for any desired product type.
- **Double hoppers**
  Two hoppers, each equipped with a level sensor, with capacities ranging from 10 to 22 liter to suit every need.
- **High-efficiency stainless steel freezing cylinders**
  Direct expansion freezing cylinders for fast, non-stop production cycles, guaranteeing maximum efficiency.
- **Photocell for smart dosing**
  Automatic recognition of cones or cups.
- **Two independent cooling systems**
  Two compressors provide a completely independent control of the two flavors: it’s like having two machines in one. Plus, whenever possible, save time and energy by using just one side.
- **Modern and compact design**
  Elegant lines and space-saving dimensions, designed to fit any environment and ensure comfortable dispensing.

		BV 261 HT	MV EASY 2	MV 255 HT	HV EASY 2
TECHNICAL SPECIFICATIONS					
Number of flavors		2+1 mix	2+1 mix	2+1 mix	2+1 mix
Control system	ECOS		•		•
	INCODIS 2.0	•		•	
Freezing cylinder feed	Gravity	•	•		
	Pump	•	•	•	•
Heat Treatment		•		•	
Size (h x w x d)		1483 x 555 x 774 mm	1522 x 640 x 797 mm	1522 x 640 x 797 mm	1522 x 640 x 916 mm
Weight		243 kg	285 kg	305 kg	316 kg
Hopper capacity	Gravity	2 x 11.5 L	2 x 18 L		
	Pump	2 x 9.8 L	2 x 15.5 L	2 x 15.5 L	2 x 22 L
Freezing cylinder capacity		2 x 1.7 L	2 x 2.6 L	2 x 2.6 L	2 x 3.5 L
PRODUCTIVE CAPACITY*					
Hourly production capacity		42 kg	58 kg	58 kg	70 kg
POWER SUPPLY					
Phase		3~	3~	3~	3~
Hertz		50 - 60 Hz	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz
Power		4500 W	5500 W	7000 W	6350 W
REFRIGERATION SYSTEM					
Cooling	Air	•	•	•	•
	Water	•	•	•	•
Number of compressors		2 x Hermetic	2 x Semi-hermetic	2 x Semi-hermetic	2 x Semi-hermetic

*Production capacity can be affected by ambient temperature, the mix used, and machine settings. The information provided is general; therefore, the specific release details should be verified. The manufacturer reserves the right to modify the specifications without prior notice.